

PROCEEDINGS

Development of a Graded Lattice Structure Design and Optimization Method with Complex Boundary Surface Constraints

Zhujiang Wang^{1,*}, Yizhou Wang¹ and Bin Zhai¹

¹ Department of Mechanical Engineering (Robotics), Guangdong Technion - Israel Institute of Technology, 241 Daxue Road, Shantou, 515063, China

*Corresponding Author: Zhujiang Wang. Email: zhujiang.wang@gtiit.edu.cn

ABSTRACT

Graded lattice structures (GLS) are used widely in the areas of 3D printed sensors, personalized wearable devices, robotics, energy absorption, etc., and have a prospective future in the field of personalized medical devices. The large-scale applications of GLS-based personalized medical devices require a GLS design method that could handle the challenges caused by diverse boundary surface constraints and various requirements of graded mechanical properties [1,2], due to patient-specific care needs. In this work, the proposed automatic seed generation algorithm-based GLS design approach is a prospective solution to promote the wide application of GLS-based personalized medical devices [3,4]. The core idea of the proposed GLS design and optimization approach is (a) using an automatic point cloud generation algorithm to generate nonuniform seed distributions inside a domain with any shape; (b) raw GLS is then generated based on the seed distribution; (c) the radius of the raw GLS is further optimized based on finite element truss analysis. As seed distributions are generated according to the required boundary shapes of the target GLS and the graded mechanical properties are optimized based on finite element analysis, the resulting GLS is guaranteed to satisfy the requirements of boundary constraints and graded mechanical properties. Finally, several demos including a 3D-printed shoe sole, a bone scaffold, and an energy absorber are created, and the results indicate that the proposed GLS design and optimization method works very well.

KEYWORDS

Lattice structure; graded lattice structure; structure optimization; finite element analysis

Funding Statement: This work was supported by the startup funding provided by Guangdong Technion - Israel Institute of Technology No. ST2100023, and Canada Research Chair in Health Care Simulation awarded to Adam Dubrowski.

Conflicts of Interest: The authors declare that they have no conflicts of interest to report regarding the present study.

References

1. Lv, Y., Wang, B., Liu, G., Tang, Y., Lu, E. et al. (2021). Metal material, properties and design methods of porous biomedical scaffolds for additive manufacturing: A review. *Frontiers in Bioengineering and Biotechnology*, 9, 1-16.
2. Pan, C., Han, Y., Lu, J. (2020). Design and optimization of lattice structures: A review. *Applied Sciences*, 10(18), 1-36.
3. Wang, Z., Srinivasa, A. R., Reddy, J. N., Dubrowski, A. (2022). PIMesh: An automatic point cloud and



This work is licensed under a Creative Commons Attribution 4.0 International License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

unstructured mesh generation algorithm for meshless methods and finite element analysis. *International Journal for Numerical Methods in Biomedical Engineering*, 38(8), e3615.

4. Wang, Z., Srinivasa, A., Reddy, J. N., Dubrowski, A. (2022). Topology optimization of lightweight structures with application to bone scaffolds and 3d printed shoes for diabetics. *Journal of Applied Mechanics*, 89(4), 1-10.